



Knowledge FOR Resilient soCiEty

2ND INTERNATIONAL SYMPOSIUM K-FORCE 2019

Tirana, September 9, 2019

INFLUENCE OF CONCRETE COVER THICKNESS ON FIRE RESISTANCE OF RC BEAMS

*Kevin Zace MSc St., Faculty of
Architecture and Engineering, Epoka
University, Albania*

*Igor Džolev PhD, Faculty of Technical
Sciences, University of Novi Sad,
Serbia*

The European Commission support for the production of this publication does not constitute an endorsement of the contents which reflects the views only of the authors, and the Commission cannot be held responsible for any use which may be made of the information contained therein.



1. Introduction


- *Fire can be regarded as the most severe condition in the life of a concrete structure.*
- *Our exposure to fire hazard is largely filtered through the built environment in which we live our lives.*
- *On this paper we are going to do different scenarios of fire in a section of a 3 m reinforced beam with the help of the Ansys software.*





2. Fire Curves

- Standard temperature-time curve (ISO 834) $\theta_{\text{E}} = 20 + 345 \cdot \log_{10}(8 \cdot t + 1)$
- External fire curve (EXT) $\theta_{\text{E}} = 660 \cdot (1 - 0.687 \cdot e^{-0.32 \cdot t} - 0.313 \cdot e^{-3.8 \cdot t}) + 20$
- Hydrocarbon fire curve (HC) $\theta_{\text{E}} = 1080 \cdot (1 - 0.325 \cdot e^{-0.167 \cdot t} - 0.675 \cdot e^{-2.5 \cdot t}) + 20$





3. Types of Heat Transfer

- Conduction
- Convection
- Radiation

➤ Equation of

$$\text{Heat Conduction} = \left[\left(\dot{q}_1 + \frac{\partial \dot{q}_1}{\partial x} \frac{dx}{2} \right) \left(\frac{\partial T}{\partial x} + \frac{\partial^2 T}{\partial x^2} \frac{dx}{2} \right) \right] - \left[\left(\dot{q}_1 + \frac{\partial \dot{q}_1}{\partial x} \frac{dx}{2} \right) \left(\frac{\partial T}{\partial x} - \frac{\partial^2 T}{\partial x^2} \frac{dx}{2} \right) \right] dy dz$$

3.1 Heat flux calculation from a

flame

- It is important to predict the radiative heat flux from a flame in determining the hazard of ignition and fire spread.
- Flames are idealized as simple geometric forms like plane layers or axisymmetric cylinders and cones in most calculations.





4 Case Study

4.1 Design of RC beam according to Eurocode standards

- *The beam cross-section dimensions are 16/30 cm with a span of 3 m.*
 $g = 8 \text{ kN/m'}$ $q = 10 \text{ kN/m'}$
- *Permanent load and Imposed load .*
- *3 reinforcement bars $\varnothing 12$*

4.2 Transient thermal analysis

- *ANSYS Workbench*
- *Material thermal properties are taken according to Eurocode 2 part 1-2 and Eurocode 3 part 1-2.*





5 Results

Standard fire curve ISO





Figure 1 – Temperature in the beam with a concrete cover of 2.2 cm at 30 min (left), 60 min (middle) and at 90 min (right) for Standard fire exposure

Figure 2 – Maximum temperature in the reinforcement bars after 90 min Standard fire exposure and fire resistance in relation to concrete cover thickness





Conclusion




Figure 3 – Fire resistance in relation to concrete cover for various types of fire exposure

6 Discussion And

- The failure criteria is when the temperature of the reinforcement reaches 550°C .
- In case of external fire curve, 2.2 cm concrete cover would be sufficient.
- The beam fire resistance would be below 90 and 60 minutes for ISO 834 and hydrocarbon fire, respectively





Co-funded by the
Erasmus+ Programme
of the European Union



Thank you
for your attention

*MSc St., Faculty of Architecture and
Engineering, Epoka University,
Albania, kzace15@epoka.edu.al*

Knowledge FOr Resilient soCiEty